



A3 colour printer with the white spot colour for printing on darker media

OKI takes graphic arts printing to a new level with the Pro9542dn, offering outstanding print quality, higher print speeds, lower total cost of ownership, complete media flexibility plus the unique option of printing with a fifth colour. You can now print on-demand, the full range of process colours, including solid white on a dark background.

Plus, the Pro9542dn is also fully compatible with EFI Fiery XF 5.0 server which enables advanced colour management, including white and process colours, optimising colour depth and print quality.

A first in digital LED printing – CMYK + White

The Pro9542dn is an affordable and unique high definition printer that enables you to not only print the full range of process colours but also offers white.

- Print in a full range of process CMYK colours
- Plus now add a spot colour - white for printing on darker media
- Stunning vibrancy of colour on dark or transparent media

Stunning high definition colour

The Pro9542dn uses the combination of digital LED technology and our Multi-Level ProQ technology to produce the sharpest and most vibrant print output available.

- Superb print resolution of 1200 x 1200dpi
- Multi-Level ProQ technology enhances colour print output
- Fully compatible with EFI Fiery® XF for advanced colour management

Low total cost of ownership

The Pro9542dn combines a highly competitive capital cost and ultra-high capacity toners cartridges to deliver a considerably reduced total cost of ownership, essential where high coverage and quality is demanded.

- Highly competitive initial capital cost
- Reduced operating costs through ultra-high capacity toner cartridges and drums
- Separate toners and drums for reduced wastage
- Energy efficient for reduced energy usage

Speed that you can rely upon

Offering the highest printing speeds on the market, the Pro9542dn delivers faster short run on-demand printing.

- Time to first print less than 8 seconds
- A3 print speeds of 28ppm in colour/mono (up to 50ppm in colour/mono for A4)
- 2GB RAM and 1.2GHz processor for rapid throughput

Media flexibility to beat all others

Beating the competition hands down when it comes to media flexibility, the Pro9542dn enables you to print in-house on a complete range of media.

- Widest paper handling from A6 to SRA3 and banner lengths up to 1.3m
- Print on paper stock up to 360gsm single sided and 320gsm duplex
- Duplex printing as standard
- Prints on a wide range of media including gloss paper, film, transfer paper, waterproof paper and more
- 530 sheet tray as standard, up to 2,950 sheets with optional trays
- Robust 300 sheet multi-purpose tray for added flexibility

A3/A4	✓
Colour/Mono	✓
Prints A6 to 1321mm, up to 360gsm	✓
White spot colour for printing on darker media	✓
1 - 30+ users	✓



PRINTER	
Print speed	A4: 50ppm colour, 50ppm mono; A3: 28ppm colour, 28ppm mono. White: up to 45ppm (simplex)
Time to first print	8 seconds colour, 8 seconds mono
Warm up time	50 seconds or less from power on
Processor speed	1.2GHz
INTERFACE AND SOFTWARE	
Connectivity	Hi-Speed USB 2.0, 10Base-T/100Base-TX/1000Base-T
Printer languages	PCL5c, PCL6 (PCL XL), Adobe PostScript 3 with direct PDF Printing (v1.7), XPS, SIDM
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: IPv4/v6, ICMP, ICMPv6, IGMP, IGMPv2, LPR, Port9100, IPP, IPPS, FTP, FTP over SSL, HTTP, HTTPS, TELNET, IPP, Auto IP, LLTD, BOOTP, DHCP, SNMPv1/v3, SNMP Trap, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, SMTP over SSL, POP3, SNTp, JCDP, FLDP, ODNsp, WSDPrint, WSD-Discovery, Web JetAdmin, NetBIOS over TCP, EtherTalk
OS Compatibility ¹	Windows Vista (32-bit & 64-bit) / XP (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Windows 7 (32-bit & 64-bit) / Server 2012 (64-bit) / Windows 8 (32-bit & 64-bit) / Windows 10 (32-bit & 64-bit); Mac OS9 / OS X 10.3.9 - 10.9
Advanced networking and security	IPv6, 802.1x authentication, SMTP Server Authentication, SNMPv3, SSL/TLS encryption, HTTPS encryption, Protocol On/Off, Protocol Port No. Change, MAC filtering, IP filtering, IP Sec, EAP-PEAP, EAP-TLS, Secure Erase ³ , Secure Print ³ , Secure Print Job Encryption ³ , Storage Devices entire Encryption ³ , Storage(HDD) Initialize (format) ³
Utility suite ¹	Print Job Accounting ² , Print Job Accounting Enterprise ² , Print Job Accounting Client, PrintSuperVision.net ² , Template Manager ² , Color Correct, Color Swatch ² , Configuration Tool, PS Gamma Adjuster, Profile Assistant (Mac Only), PDF Direct Print, EFI Fiery XF Server Option (External color management server)
TYPEFACES	
Printer fonts	87 scalable PCL fonts, Lineprinter/OCR-A/OCR-B/USPSZIP bit-map fonts, 10 TrueType fonts, 136 Adobe PostScript Type 1 fonts
Barcode	UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved 2of5, Code39, Code128, EAN/UCC-128, CODABAR, ZIP+4 POSTNET: PDF417/QR code 2D barcodes
PRINT QUALITY	
Resolution	ProQ4800 Multi-level technology, 1200 x 1200dpi
Enhancements	Auto Colour Balance, Auto Registration, Auto Media Detect
PAPER HANDLING	
Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 300 sheets of 80gsm
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; High Capacity Feeder: 1,590 sheets of 80gsm
Maximum paper capacity	2,950 sheets of 80gsm
Paper sizes	Tray 1/2/3: A3, SRA3 (up to 330 x 457mm), SRA4, A4, A5, A6, B4, B5, B6; Multi-purpose tray: A3, SRA3, SRA4, A4, A5, A6, B4, B5, B6 Custom size: Width 64 - 330mm Length 89 - 1,321mm; High Capacity Feeder: A3, SRA3 (up to 328 x 457mm), SRA4, A4, A5, A6, B4, B5, B6
Paper weight	Tray 1/2/3: 52 to 320gsm; Multi-purpose tray: 52 to 360gsm; Duplex: 64 to 320gsm; High Capacity Feeder: 52 to 320gsm
Duplex	Standard
Paper output	610 sheets face down tray, 300 sheets face up tray

¹Check local OKI website for latest driver releases and OS compatibility; ²Windows only; ³HDD required; ⁴Including all consumables;

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

OPERATOR PANEL	
LCD Display	10.9cm Colour Graphic LCD (480x272 dots)
GENERAL FEATURES	
Memory	Standard RAM: 2GB; Maximum RAM: 2GB Optional Hard Disk Drive: 160GB
Environment	Operating temperature/humidity: 10°C to 35°C (17°C to 27°C recommended) / 10% to 85% RH (50% to 70% RH recommended) Storage temperature/humidity: -10°C to 43°C, 10% to 90%RH
Power supply	Single phase 220 to 240VAC, frequency 50Hz +/- 2Hz
Power consumption	Typical: 1100W; Max: 1600W; Idle: 40W (average); Power Save: <34W; Deep Sleep: <4W; Off Mode: <0.5W
Noise level	Operating: 57dB(A); Standby: 32dB(A) or less; Power save: Inaudible
Dimensions (HxWxD)	640 x 699 x 625mm
Weight ⁴	110.8kg
Duty Cycle	Average: 25,000 pages/month; Maximum: 300,000 pages/month
Warranty	3 years extended warranty upon registration within 30 days of purchase
Product order number	Pro9542dn: 45530622
ACCESSORIES (ORDER NUMBERS)	
2nd/3rd paper tray	45530703
2nd/3rd paper tray with castor	45530903
High Capacity Feeder	45530803
Hard Disk Drive	160GB: 44622302
EFI Fiery XF 5.0	Contact Oki for more information
Cabinet	45980001
Banner Tray	45531003
CONSUMABLES (ORDER NUMBERS)	
Toner cartridge* (42,000 pages)	Cyan: 45536555; Magenta: 45536554
Toner Cartridge* (24,000 pages)	Yellow: 45536437
Toner Cartridge* (51,000 pages)	Black: 45536556
Toner Cartridge (15,000 pages)	White: 45536543
Image drums** (40,000 pages)	Cyan: 45103721; Magenta: 45103720; Yellow: 45103719; Black: 45103722
Image drum** (20,000 pages)	White: 45103765
Transfer Belt (150,000 pages)	45531223
Fuser Unit (150,000 pages)	45531113
Waste Toner Box (40,000 pages)	45531503

*Toner: Number of A4 pages @ ISO coverage. Printer shipped with toner for 24,000 pages CMY, 38,000 pages K @ ISO and 10,000 pages W @ 5%.

**Drum: Average number of A4 pages printed.

3 Year Warranty

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer.

For further information please visit: www.okiwarranty.com/3YEAR
Without registration, the standard pan-European 1 year warranty applies.



Digital Signage Systems

HP Latex/ Plotter/ Photo Printers, Xerox Digital Printers,
Finishing Equipment, Signage Production Solutions,
Computing, Software & Service Solutions

471- 2474770/11, info@dsssouth.in, www.dsssouth.in

OKI EUROPE LTD.

Blays House, Wick Road
Egham, TW20 0HJ
United Kingdom
T +44(0) 20 8219 2190
F +44(0) 20 8219 2199
www.oki.com/eu

OKI

Open up your dreams